



**MG300/400**

## Features

**MG180/300** for layer windings with automatic wire-guide.  
**MG300/400** for layer windings with automatic wire-guide.

## Tech specs

Tecnichal data	MG180/300	MG300/400
ø wire (mm)	0.02÷2.00	0.02÷5.00
Max ø coil (mm)	180	300
Max lenght coil (mm)	300	400
Distance between centres (mm)	180÷300 increased lenght on request	200÷400 increased lenght on request
Speeds (rpm)	I 0÷1000 II 0÷4500	I 0÷500 II 0÷2250
Motors	Brushless	
Gearbox	Belts	
Complete frame	Aluminum	
Feeding line	1x230V 50/60Hz 1,7KW	3x400V 50/60Hz 3KW
Dimensions (mm)	1100x950x1650	1250x950x1650
Net weight (Kg)	150	190

## Standard accessories and optionals

MG180/300	MG300/400
N°1 computer with lcd display 5" 256 colors 800x480 touch screen, memory card	
N°1 brushless spindle motor with brake and digital driver	
N°1 brushless wire-guide motor with digital driver	
N°1 table	
N°1 CE safety guard	
<b>Optionals</b>	
Tensioners	
Wire-guides for the simultaneous winding of several bobbins	
<small>IN REASON OF EVOLUTION OF REGULATIONS AND MATERIALS, THE CHARACTERISTICS AS ABOVE REFERRED WILL BE CONSIDERED BINDING ONLY AFTER MANUFACTURER'S CONFIRMATION</small>	

You will find more details on:

[IMPEMASRL.COM](http://IMPEMASRL.COM)



**IMPEMA S.R.L.**

Via Europa 1, 20020 Magnago (MI) -ITALY-  
T. +39 0331 657500

E. [info@impemasrl.com](mailto:info@impemasrl.com) W. [impemasrl.com](http://impemasrl.com)