

**MG 1900**



**MG 2000**



## Features

**MG 1900** for electric motor coil, without automatic wire-guide.

**MG 2000** for layer windings and electric motor coil, without automatic wire-guide.

## Tech specs

Tecnichal data	MG 1900	MG 2000
Max ø coil (mm)	1900	
Max lenght coil (mm)	300	2000
Max weight coil (kg)	150	600
Max torque (Kgm)	650	
Speeds (rpm)	0÷373	
Motor with inverter	3 KW 400V 50/60 Hz 1500rpm C.I.F. IP55	
Gearbox	Gearbox in oil	
Complete frame	Steel	
Feeding line	3x400V 50/60Hz 4KW	
Dimensions (mm)	800x650x1370	3500x800x1370
Net weight (Kg)	600	1050

## Standard accessories and optionals

MG 1900	MG 2000
N°1 rectangular faceplate 550mm	N°1 faceplate Ø 400mm
	N°1 revolving center CM5
N°1 digital preset counter	
N°1 inverter with electronic foot-pedal	
N°1 electromegnetic brake	
N°1 safety guard	
<b>Optionals</b>	
Rectangular faceplate 850mm	
Set of straight arbors/Set of concentric arbors	
Kit motor coils (n°1 pair of square mandrels and n°1 wire-guide with rod)	
Microprocessing electronic counter to memorize more programs	
	Vice to grip the core of transformers
<small>IN REASON OF EVOLUTION OF REGULATIONS AND MATERIALS, THE CHARACTERISTICS AS ABOVE REFERRED WILL BE CONSIDERED BINDING ONLY AFTER MANUFACTURER'S CONFIRMATION</small>	

You will find more details on:

**IMPEMASRL.COM**



**IMPEMA S.R.L.**

Via Europa 1, 20020 Magnago (MI) -ITALY-  
T. +39 0331 657500

E. [info@impemasrl.com](mailto:info@impemasrl.com) W. [impemasrl.com](http://impemasrl.com)