



## Features

**MG 950** for linear windings with automatic wire-guide.

Technical data	MG 950
Max.diameter windings (mm)	500
Max. lenght windings (mm)	900
Max. weight windings (kg)	300
Speed (r.p.m.)	0÷500
Winding pitch (mm)	0,10÷30,0
Frame	Steel
Feeding line	3x400V 50/60Hz 5 KW
Dimensions (mm)	2300x1300x1700
Weight (Kg)	520

## Standard accessories and optionals

### MG 950

N°1 self-centering chuck Ø160mm and n°1 revolving center

N°1 electromegnetic brake

N°1 CNC with 7" 256 color 800x480 touch screen LCD display, unlimited SD memory

N°1 spindle brushless motor with digital driver

N°1 wire-guide brushless motor with digital driver

N°1 safety guard

### Optionals

Unwinders/tensioners

Pneumatic tailstock

Vice to grip the core of transformer

IN REASON OF EVOLUTION OF REGULATIONS AND MATERIALS, THE CHARACTERISTICS AS ABOVE REFERRED WILL BE CONSIDERED BINDING ONLY AFTER MANUFACTURER'S CONFIRMATION

You will find more details on:

[IMPEMASRL.COM](http://IMPEMASRL.COM)



**IMPEMA S.R.L.**

Via Europa 1, 20020 Magnago (MI) -ITALY-  
T. +39 0331 657500

E. [info@impemasrl.com](mailto:info@impemasrl.com) W. [impemasrl.com](http://impemasrl.com)